

**15-DAY COMMENT PERIOD MODIFICATIONS  
FOR  
PROPOSED PLUMBING STANDARDS  
OF THE  
DIVISION OF THE STATE ARCHITECT - ACCESS COMPLIANCE  
REGARDING THE ADOPTION BY REFERENCE OF THE  
2006 EDITION OF THE UNIFORM PLUMBING CODE (UPC)  
INTO THE 2007 CALIFORNIA PLUMBING CODE  
CALIFORNIA CODE OF REGULATIONS TITLE 24, PART 5**

---

**Legend for Express Terms:**

1. California amendments brought forward without modification: *All such language appears in Italics.*
  2. California amendments brought forward with modification: *All such language appears in Italics, modified language is underlined.*
  3. New UPC language with new California amendment: UPC language is shown in normal Arial 9 pt. California amendments to UPC text appear underlined and in italics.
  4. New California amendment: California language appears underlined and in Italics.
  5. Repealed text: Shown as ~~Strikeout~~.
  6. 15-Day modification Repealed text: Shown as ~~Strikeout~~.
  7. UPC text proposed to be removed: Shown as ~~Strikeout~~.
  8. 15-Day modifications: Shown as ~~Strikeout~~ or underlined.
- 

**ITEM # 06/06 PART 5**

**General -- Application.** DSA/AC proposes to remove the general application statement, "for applications listed in Section 109.1 regulated by the Division of the State Architect/Access Compliance", and replace with the DSA/AC acronym, "[For DSA/AC]", where required throughout this document.

Authority Cited – GC§ 4450.

Reference – GC §§ 4450 through 4461, 12955.1(d) and H&SC§§ 18949.1, 19952 through 19959.

**Rationale:** This change is required for consistency with the Building Standards Commission format.

**ITEM # 06/06 PART 5**

**Chapter 4, Table 4-1, Minimum Plumbing Facilities.** DSA/AC proposes to correct a typographical error in this section by adding italics to the previously proposed preemptive editorial amendment.

Authority Cited – GC§ 4450.

Reference – GC §§ 4450 through 4461, 12955.1(d) and H&SC§§ 18949.1, 19952 through 19959.

**Rationale:** Italics were inadvertently omitted during preparation of the document. Criteria #1 & 8.

**TABLE 4-1 Minimum Plumbing Facilities<sup>1</sup>**

Each building shall be provided with sanitary facilities, including provisions for persons with disabilities as prescribed by the Department Having Jurisdiction. For requirements for persons with disabilities, ~~ICC/ANSI A117.1 Accessible and Usable Buildings and Facilities~~, Chapter 11A or 11B of the California Building Code, may ~~shall~~ be used.

The total occupant load ...

The occupant load ...

## ITEM # 06/06 PART 5

**Chapter 4, Section 411.7 & 412.11.** DSA/AC proposes to add titles to this Express Terms item to clearly identify which 2001 CPC section is proposed for relocation and repeal, which section is proposed for relocation and adoption, and the location of these sections in the 2007 CPC. DSA/AC also proposes to correct the typographical error in the DSA/AC acronym which appears in 2007 CPC, Section 412.1.

Authority Cited – GC§ 4450.

Reference – GC §§ 4450 through 4461, 12955.1(d) and H&SC§§ 18949.1, 19952 through 19959.

**Rationale:** As presented in the current Express Terms, there is confusion about where the relocated 2001 CPC Section 101.4.1.1.3.1 will actually appear in the 2007 CPC. Criteria #1 & 8.

### 411.0 Floor Drains and Shower Stalls.

**411.7** All shower compartments, regardless of shape, shall have a minimum finished interior of one thousand twenty-four (1,024) square inches (0.66 m<sup>2</sup>) and shall also be capable of encompassing a thirty (30) inch (750 mm) circle. The minimum required area and dimensions shall be measured at a height equal to the top of the threshold and at a point tangent to its centerline. The minimum area and dimensions shall be maintained to a point seventy (70) inches (1778 mm) above the shower drain outlet with no protrusions other than the fixture valve or valves, shower head, soap dishes, shelves, and safety grab bars or rails. Fold-down seats in accessible shower stalls shall be permitted to protrude into the thirty (30) inch (750 mm) circle.

**Exception No. 1:** Showers that are designed to comply with ~~ICC/ANSI A117.1~~ Chapter 11A or 11B, of the California Building Code.

**Exception No. 2:** The minimum required area and dimension shall not apply where an existing bathtub is replaced by a shower receptor having minimum overall dimensions of 30 inches (750 mm) in width and 60 inches (1,500 mm) in length.

(Relocated from 2001 CPC, Section 412.0, Floor Drains and Shower Stalls.

~~Note: [For DSA/AC] See Part 2, Chapters 11A and 11B for shower compartment size for accommodation of persons with disabilities.~~

### 412.0 Minimum Number of Required Fixtures.

#### 412.1 Fixture Count. ...

(Relocated from Section 101.4.1.1.3.1)

~~101.4.1.1.3.1 [For DSA/AC] 412.1.1.~~ *Effective January 1, 1990, in new construction and those existing facilities which occupancy type are listed in Tables 4-1 and 4-4 for public use, which apply for permit to undertake construction, structural alterations, repairs or improvement which exceed 50 percent of the square footage of the entire facility, shall install water closets, urinals, lavatories and drinking fountains as stipulated in Tables 4-1 and 4-4 for public use. Community and/or municipal parks with a bleacher capacity not exceeding 500 seats shall be exempt from the requirements of this section and Tables 4-1 and 4-4.* ~~Note: 2. Each bathroom shall comply with Part 2, Chapters 11A and 11B of the California Building Code.~~